



KEY POINTS

- Very sturdy housing structure with 3 thick beams
- 4-row rotor equipped with Y cutters
- Power transmission via oversize gearbox, shaft and trumpets
- Reversible Y cutters mounted onto treated bushes
- Optional: rear roller with mud scraper; heavy duty type pallet cutters

SPECIFICATIONS

WORKING WIDTH	SINGLE DRIVE <i>Fixed or offset model (except 2.40m)</i>						DOUBLE DRIVE <i>fixed or offset model</i>	
	2.40		2.80		3.20		2.80	3.20
PTO speed (rpm)	540	1000	540	1000	540	1000	1000	
Number of belts	4		5		5		2 x 3	
Tractor power rating (depending on PTO) (hp)	70-200			90-200				
Coupling	For welded fixed coupling						For fixed coupling, Centred, bolted on and adjustable in depth	
Coupling category	Cat. 2 clevis hitch							
Number of cutters (in Y)	56		64		76		64	76
Counter-cutter	Upper and lower, U-shaped, removable							
Adjustable terrain tracking	Pair of semi-pivoting wheels - Pair of bolt-on skids in							
Rear cover	Mobile cover							
Housing thickness (mm)	4							
Armour plate (mm)	As standard on the housing - Bolt-on - Thickness 4							
Weight *(kg)	1220		1400		1504		1610	1730

*Add 160 kg for offset models

OPTIONS

Several cutter assemblies	Hardox armour plates
Front chain curtains	Hydraulic cover
Rear wheel with assisted adjustment	Meter and signalling kit