



## KEY POINTS

- Oversize chassis composed of bushed pivots
- Patented protection for side transmission systems
- 1 Pair of pivoting twin wheels with damper and 1 pair of single wheels
- Rotor equipped with Y cutters + fan
- Optional: edging shredder and roller with mud scraper

## SPECIFICATIONS

WORKING WIDTH	(M)	4.80	6.40
PTO speed	(rpm)	1000	
Number of belts		2 x 5	
Tractor power rating	(hp)	130-300	160-300
Coupling category		Cat. 3 clevis hitch	
Number of cutters	(Y+ fan)	104 Y + 52 fans	136 Y + 68 fans
Counter-cutter		Upper and lower removable combs	
Adjustable terrain tracking		1 Pair of semi-pivoting twin wheels with damper Pair of bolt-on skids in <b>HARDOX</b>	1 Pair of semi-pivoting twin wheels with damper and 1 pair of single wheels Pair of bolt-on skids in <b>HARDOX</b>
Rear covers		Mobile covers	
Housing thickness	(mm)	4	
Armour plate	(mm)	Standard - bolt-on - Thickness 4	
Weight	(kg)	3470	4010

## OPTIONS

Chain curtains	Edging shredder with hydraulic lifting
Roller with mud scraper	Flow regulator
<b>HARDOX</b> armour wear plate	Surface area meter