



KEY POINTS

- Oversize chassis composed of bushed pivots
- Patented protection for side transmission systems
- Roller with integrated, removable sealed end caps
- Hydraulic folding shredder
- Large diameter rotor equipped with heavyweight B1 hammer cutters
- Front element can be used solo, in push or pull mode

SPECIFICATIONS

WORKING WIDTH	(M)	REAR ELEMENT	FRONT ELEMENT (COMBINED MASTER-FIELD - PUSH - PULL)	
		8.00	2.80	3.10
PTO speed	(rpm)	1000		
Number of belts		5	5	5
Tractor power rating	(hp)	160-280	80-220	90-220
Coupling		Fixed	Hydraulic offset on slide	
Coupling category		Cat. 3 clevis hitch	Cat. 2 clevis hitch - Floating position	
Number of hammer cutters	(B1)	2 x 34	30	34
Counter-cutter		Upper and lower, U-shaped, removable		
Adjustable terrain tracking		Ø 220 roller - Pair of skids with bolt-on base plate in HARDOX		
Rear covers		Mobile covers	Closed housing	
Housing thickness	(mm)	6		
Armour plate	(mm)	As standard on the housing - Welded - Thickness 4		
Weight	(kg)	3100	1515	1600

OPTIONS

Chain curtains	Roller mud scraper
Pairs of single or twin wheels	Hardox armour plates
Additional transmission	Time and surface area meter