



KEY POINTS

- Large diameter rotor tube
- Very sturdy housing equipped with bolt-on armour plates
- Reversible Y cutters or pallet cutters mounted onto treated bushes
- 2-part mobile rear cover
- Semi-pivoting wheels with sculpted, off-road tyres

SPECIFICATIONS

	MONOROTOR				BIOTOR	
	3.20		4.00		4.80	
WORKING WIDTH	3.20		4.00		4.80	
Rotor model	4 rows	10 rows	4 rows	10 rows	4 rows	10 rows
PTO speed (rpm)	1000					
Tractor power rating (hp)	100-280			120-280		
Coupling	Centred and bolted					
Coupling category	Cat. 2 clevis hitch					
Number of cutters (in Y)	76	120	96	160	112	200
Counter-cutter	Upper and lower removable combs					
Adjustable terrain tracking	2 semi-pivoting wheels			3 semi-pivoting wheels		
Rear cover(s)	Mobile cover(s)					
Housing thickness (mm)	6					
Armour plate (mm)	As standard on the housing - Bolt-on - Thickness 4					
Weight (kg)	2050	2170	2280	2450	2710	2865

OPTIONS

Pallet cutter configuration	Rear roller with mud scraper
Front chain curtains	Hydraulic cover
Lengthwise transport on 4.00 m and 4.80m models	Armour plate