



## KEY POINTS

- Quick and easy hydraulic lifting system on a rocker arm with connecting rods
- Oversize central box
- Identical alignment of the coupling head pivot axis and the wide-angle transmission
- 5-rotor assembly with deflectors and counter-cutters
- Damper on KEVLAR-reinforced side wheels, side elements and rocker arm

## SPECIFICATIONS

|                             |  |   |                                   |
|-----------------------------|--|---|-----------------------------------|
| WORKING WIDTH               |  | <b>4.80</b>   | <b>6.40</b>                       |
| Overall depth (m)           |  | 4.45  | 4.65                              |
| PTO speed (rpm)             |  | <b>1000</b>   |                                   |
| Min. tractor power (hp)     |  | 85-240  | 140-350                           |
| Main transmission           |  | Wide angle (homokinetic) - Star tube  |                                   |
| Cat. 2 coupling             |  | Pivoting clevis hitch   |                                   |
| Rotor                       |  | 5 rotors - Single blade - 2 cutters   | 5 rotors - Triangular - 3 cutters |
| Adjustable terrain tracking |  | Wheels - Side skids with bol-on wear-resistant plates in <b>HARDOX</b><br><small>WEAR PLATE</small> |                                   |
| Cutting height (mm)         |  | 30 to 280   |                                   |
| Weight (kg)                 |  | 3700  | 3950                              |

## OPTIONS

Set of upper cutters  
Blower with flow regulator  
Rubber flap

Pivoting front wheels  
Time and surface area meter